

LX500 Color Label Printer Specifications

Print Method:	Inkjet
Print Resolutions:	4800 x 1200 dpi, 1200 x 1200 dpi, 600 x 600 dpi
Ink Cartridge:	Color (CMY)
Colors:	16.7 million
Color Matching:	Z-Color™ Color Matching Software
Print Width:	0.75" (19mm) to 4.25" (108mm)
Print Length:	0.75" (19mm) to 24" (609.6mm)
Media Width:	1" (25.4mm) to 4.25" (108mm)
Media Types:	Roll-fed pressure-sensitive labels, roll-fed tags, fan-fold labels or tags
Media Sensing:	Moveable see-through sensor for die-cut labels; Reflective for labels and tags with black stripe; Continuous label stock; Preprinted label stock.
Supply Roll:	5" (127mm) maximum diameter on 2" (50.8mm) core. Core has additional restrictions - see manual.
Ink Level Warning:	Calculates actual number of prints remaining based upon ink usage of graphics being printed (patent-pending)
Indicator Lights:	Power, Ink
Controls:	Pause, Load/Feed, Unload
Operating Systems:	Windows® 7/8/10+ (Coming Soon - Mac OS X 10.7 or higher)
Recommended Minimum System:	For PC: Pentium® IV computer or better, 512MB RAM, 5GB free hard drive space, USB 2.0 or USB 1.1
Label Design Software:	BarTender UltraLite Primera Edition included. Can also be used with most other popular label design and graphics software programs.
Electrical Rating:	12VDC, 5.0A
Power Requirements:	100-240VAC, 50/60 Hz, 60 watts
Certifications:	UL, UL-C, CE
Weight:	7.0 lbs. (3.2 kg)
Dimensions:	10.4"W x 15.3"D x 7.1"H (closed), 17.4"(open) 264mmW x 389mmD x 180mmH (closed), 442mmH (open)
Options:	Ink Cartridge, Tri-Color #53374 or #53376(slower speed). LX500 #74273 LX500c #74275 (w/ cutter)